



### Kvaser Linx J1587

EAN: 73-30130-00389-7

Kvaser Linx is a single channel, add-on cable that provides access to a J1587 bus network. It connects to your existing Kvaser High Speed CAN interface or Datalogger in series. Compatible with selection of Kvaser CAN HS devices.

#### Major Features

- Works with most Kvaser CAN HS interfaces (Not compatible with Memorator Professional 5xHS).
- Create software applications using the included J1587 library.
- Supports data logging with the Kvaser Memorator Professional HS/HS.
- Log both CAN and J1587 data simultaneously.
- Trigger on J1587 MID, PID, etc.
- Molded 9 pin DSUB female connector with thumbscrews.
- Molded 9pin DSUB male connector.
- Compact plastic housing.

## Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

## Support

- Free Technical Support on all products available by contacting support@kvaser.com.

## Software

- Documentation, software and drivers can be downloaded for free at [www.kvaser.com/downloads](http://www.kvaser.com/downloads).
- Kvaser CANLIB SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, and Visual Basic.
- All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!
- J2534 Application Programming Interface available.
- RP1210A Application Programming Interface available.
- On-line documentation in Windows HTML-Help and Adobe Acrobat format.

TECHNICAL DATA - KVASER LINX J1587

ERROR COUNTERS READING	No
ON-BOARD TX BUFFER	No
PC INTERFACE	Cable
MINIMUM BITRATE (KBPS)	9600
CASING MATERIAL	-
MSGRATE RX MAX	2000
GALVANIC ISOLATION	No
STATUS	Active
SILENT MODE	No
ON-BOARD BUFFER	No
LENGTH (MM)	100
RUGGED	No
ERROR FRAME GENERATION	No
# OF CAN CHANNELS	1
MSGRATE TX MAX	2000
MAXIMUM BITRATE (KBPS)	9600
CERTIFICATIONS	CE,RoHS
SOUND	No
ON-BOARD RX BUFFER	No



## Kvaser Linx J1587

TIMESTAMP RESOLUTION (US)	100
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
WEIGHT (G)	100.0
WIDTH (MM)	25
ERROR FRAME DETECTION	No
HEIGHT (MM)	20

The information herein is subject to change without notice