



Kvaser Leaf Professional HS OBDII

EAN: 73-30130-00404-7

Kvaser Leaf Professional is a one channel, high performance, USB interface for High Speed CAN. The OBDII connector provides easy access to vehicle diagnostics from the PC. Includes Kvaser's patented MagiSync feature for synchronized time-stamping, Galvanic Isolation for protection against voltage spikes, and Auto Transmit for placing messages on the bus at set intervals.

Major Features

- Interfaces the CAN bus with an OBD2 connector.
- Supports High Speed CAN (ISO 11898-2)
- Handles up to 20,000 messages per second, time-stamped and synchronized with a precision of 1 microsecond.
- Auto transmit buffers, to send messages on a defined interval.
- Auto response buffers, to send messages on a defined event.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- Excellent error handling.

- Supports silent mode for analyzing tools.
- Low power consumption.
- Excellent EMC performance.
- Polyurethane cabling for extreme environments.
- Galvanic isolation of the CAN bus driver stage to protect the hardware.
- Labeled CAN channel for easy identification of the supported physical layer.
- Equipped with a 110 cm (44 in.) long USB cable and a 30 cm (12 in.) long CAN cable.
- Designed for USB 2.0, backward compliant with USB 1.1.
- Quick and easy Plug-and-Play installation.
- A practically unlimited number of Kvaser Leafs can be connected via standard USB hubs for simultaneous use on a single PC.

Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

Support

- Free Technical Support on all products available by contacting support@kvaser.com.

Software

- Documentation, software and drivers can be downloaded for free at www.kvaser.com/downloads.
- Kvaser CANLIB SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, and Visual Basic.
- All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!
- J2534 Application Programming Interface available.
- RP1210A Application Programming Interface available.



Kvaser Leaf Professional HS OBDII

- On-line documentation in Windows HTML-Help and Adobe Acrobat format.

TECHNICAL DATA - KVASER LEAF PROFESSIONAL HS OBDII

WEIGHT (G)	100.0
TIMESTAMP RESOLUTION (US)	1
MSGRATE TX MAX	20000
WIDTH (MM)	25
GALVANIC ISOLATION	Yes
EMBEDDED SCRIPT	No
MAXIMUM BITRATE (KBPS)	1000
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
ON-BOARD TX BUFFER	Yes
API, LICENCED	None
ON-BOARD RX BUFFER	Yes
ERROR COUNTERS READING	Yes
CASING MATERIAL	-
OPERATING SYSTEM	Win Vista,Win 8,Win 7,Win XP
API, FREE	Kvaser API, J2534, RP 1210
CERTIFICATIONS	RoHS
ERROR FRAME GENERATION	Yes
MINIMUM BITRATE (KBPS)	5
SOUND	Yes
# OF CAN CHANNELS	1
LENGTH (MM)	100
MSGRATE RX MAX	20000
CONNECTOR	N/A
CLOCK SYNC	Yes
PC INTERFACE	USB
SILENT MODE	Yes
NETWORK CHANNEL(S)	1 x CAN HS



Kvaser Leaf Professional HS OBDII

RUGGED	No
ON-BOARD BUFFER	Yes
HEIGHT (MM)	20
IP CLASS	N/A
ERROR FRAME DETECTION	Yes
STATUS	Active

The information herein is subject to change without notice